

GAS R134a
M/HBP (media-alta presión) de retorno

CAPACIDAD DE ENFRIAMIENTO ASHRAE

CÓDIGO ERO	MODELO	TIPO DE MOTOR	HP	D	TENSIÓN / FRECUENCIA NOMINAL	BTU/s	LRA	CAPACIDAD DE ENFRIAMIENTO ASHRAE											
								-15° C (5° F)	-10° C (10° F)	-5° C (23° F)	0° C (32° F)	0° C (32° F)	7.2° C (23° F)	10° C (32° F)	10° C (32° F)	10° C (32° F)	10° C (32° F)	10° C (32° F)	10° C (32° F)
CMFR134AP013	AWQ110HDG	CSIR	1/3 HP	11.0 cm3	110-120V / 50-60Hz	4418 BTUs	28.5	507	1730	650	2218	809	2760	979	3255	1175	4008	1295	4418
CMFR134AP014	AWQ91HDG	CSIR	1/4 HP	9.1 cm3	110-120V / 50-60Hz	3753 BTUs	25	430	1467	551	1880	683	2330	828	2798	996	3397	1100	3753



CÓDIGO ERO	ACCESORIOS DE ARRANQUE		
	PROTECTOR TERMICO	RELAY	CAPACITOR DE ARRANQUE (UF)
CMFR134AP013	Tipo KLIXÓN	Tipo DANFOSS	161-193uF / 110V
CMFR134AP014	Tipo KLIXÓN	Tipo DANFOSS	161-193uF / 110V

D = DESPLAZAMIENTO LRA = AMPERAJE DE ROTOR BLOQUEADO (MOTOR DETENIDO)

